



Sprung Boundary Posts - Anti Rust Coating

Ex. VAT: £85.25 TOTAL Inc.
VAT: £102.30

*Base price, not including any custom options.

Product Images





Description

A sprung boundary post available ragged for casting in or flanged for bolting down.

Specification

- Height 750mm
- Diameter 48mm
- Wall thickness 3.25mm
- Gross weight 3.5kgs
- Spring allows post to return to position after light impact
- Weather cap of Black Polypropylene
- Wall thickness 3.25mm
- Will spring approx 30 degrees from the vertical

Installation

Flanged posts should be bolted on to a suitable existing surface, preferably concrete (bolts available extra). Ragged posts should be cast into a concrete foundation approx 300mm cube. The ragged ends ensure a good anchorage into concrete. Flanges require 3 quantity 12mm bolts. The flange plate is approx 6mm thick, 134mm diameter. Ragged version is 240mm below ground and is splayed for firm ground anchorage. Recommended centres for posts to prevent vehicle access is 1.3m.

Buy more than 30 and get a greater discount. Please call us.

Delivery

Typical delivery time: 5-7 working days

Additional Information

Best Sellers M2	No
-----------------	----

Additional Options

Bollard Options	Galvanised fixed (Ragged)	£0.00
	Painted fixed (Ragged) RAL Colour	£23.36
	Galvanised Removable (Flanged)	£0.00
	Painted Removable (Flanged) RAL Colour	£5.84
Fixing Bolts	No Bolts	£0.00
	Pack of 3 bolts	£5.84

